

**id:** pc2009  
**description:** Desktop Computer  
**product:** OEM  
**vendor:** OEM  
**version:** OEM  
**serial:** OEM  
**width:** 32 bits  
**capabilities:** smbios-2.5 dmi-2.5 smp-1.4 smp  
**configuration:** boot = normal  
chassis = desktop  
cpus = 4  
uuid = 9F2C3B36-1DDC-58B1-DF94-001FE2655D26

**id:** core  
**description:** Motherboard  
**product:** G31MX Series  
**vendor:** Foxconn  
**physical id:** 0  
**serial:** UY30835064195

**id:** firmware  
**description:** BIOS  
**vendor:** Phoenix Technologies, LTD  
**physical id:** 0  
**version:** 6.00 PG (07/30/2008)  
**size:** 128KiB  
**capacity:** 448KiB  
**capabilities:** isa pci pnp apm upgrade shadowing cdboot bootselect socketedrom edd  
int13floppy360 int13floppy1200 int13floppy720 int13floppy2880  
int5printscreen int9keyboard int14serial int17printer int10video acpi usb  
ls120boot zipboot biosbootspecification

**id:** cpu:0  
**description:** CPU  
**product:** Intel(R) Core(TM)2 Quad CPU Q8200 @ 2.33GHz  
**vendor:** Intel Corp.  
**physical id:** 4  
**bus info:** cpu@0  
**version:** 6.7.7  
**serial:** 0001-0677-0000-0000-0000-0000  
**slot:** Socket 775  
**size:** 1998MHz  
**capacity:** 4GHz  
**width:** 64 bits  
**clock:** 333MHz  
**capabilities:** boot fpu fpu\_exception wp vme de pse tsc msr pae mce cx8 apic sep mtrr  
pge mca cmov pat pse36 clflush dts acpi mmx fxsr sse sse2 ss ht tm pbe  
nx x86-64 constant\_tsc arch\_perfmon pebs bts pni monitor ds\_cpl est tm2  
ssse3 cx16 xtpr sse4\_1 lahf\_lm cpufreq  
**configuration:** id = 0